

WEIGHT INDICATOR: WI-2013L



This is a micro controller based Indicator unit. It is highly versatile, accurate. It displays engineering value of analog signal (mV) input from the load cell.

Features:

- ◆ On-board high resolution ADC.
- ◆ Filtering: Analog & Digital
- ◆ Sampling: 15 readings/second
- ◆ Power Supply: 110-230VAC, 50 Hz.
- ◆ Input: 4-wire Loadcell, Upto Four Single Load cell with 300 Ohms Resistor
- ◆ Options:
 - Outputs: Six Relay outputs
 - Retransmission: 4-20 mA/0-10V Proportional indicated weight
 - RS-232/485 Serial Port for communication with remote display/ Printer/ Computer
- ◆ Remote input for GROSS/NET, TARE and Zero functions
- ◆ Display: 20 Character x 4 Line LCD with back lit
- ◆ Key board: Six keys membrane like
- ◆ Programmable Parameters:
 - Decimal Point, Capacity, Display Resolution, Grad, Zero Track Band, Zero Range
- ◆ Configuration Data are stored in serial NVRAM, Battery back up not required
- ◆ Calibration through front keypad (Offset: 'Z' & Span: 'S' stored in NVRAM)
- ◆ Different Password for Calibration & normal operation
- ◆ Enclosure: Metallic, Powder coated, General Purpose, Panel Mounting type
- ◆ Dimension:
 - Outer: 192 mm (W) x 96 mm (H) x 110 mm (D)
 - Cutout: 186 mm (W) x 92 mm (H)

Samyak Instrumentation Pvt. Ltd.

F/4, Memnagar Complex, Opp. Petrol Pump, Memnagar, Ahmedabad-380 052, India

Phone: 91-79-27495500/5600 Fax: +91-79-27417997

E-mail: sales@samyak.com url: www.samyak.co.in
