

WEIGHT INDICATOR: SMIT 3015 S

This is a microcontroller based Indicator unit. It is highly versatile, accurate. It displays Engineering value of analog signal (mV) input From the load cell



Features:

- On-board high resolution ADC.
- Filtering: Analog & Digital
- Sampling: 15 readings/second
- Power Supply: 110-230VAC, 50 Hz.
- Input: 4-wire Load cell, Up to Four Single Load cell with 300 Ohms Resistor
- Options:
 - Outputs: Four Relay outputs
 - Retransmission: 4-20 mA/0-10V Proportional indicated weight
 - RS-232/485 Serial Port for communication with remote display/ Printer/ Computer
- Remote input for GROSS/NET, TARE and Zero functions
- Display: 6-digit 7-segment 0.56" Red LED
- Key board: Four keys membrane like
- Programmable Parameters:
 - Decimal Point, Capacity, Display Resolution, Grad, Zero Track Band, Zero Range
- Configuration Data are stored in serial NVRAM, Battery backup not required
- Calibration through front keypad(Offset: '**Z**' & Span: '**S**' stored in NVRAM)
- Different Password for Calibration & normal operation
- Enclosure: Metallic, Powder coated, General Purpose, Panel Mounting type
- Dimension:
 - Outer: 96 mm (W) x 96 mm (H) x 110 mm(D)
 - Cutout: 92 mm (W) x 92 mm (H)

Samyak Instrumentation Pvt. Ltd.

F/4, Memnagar Complex, Opp. Petrol Pump, Memnagar, Ahmedabad-380 052, India

Phone: 91-79-27495500/5600 Fax: +91-79-27417997

E-mail: sales@samyak.com url: www.samyak.co.in
