

Weight Indicator: SMIT-3016



This is a microcontroller based Indicator unit. It is highly versatile, accurate and different from the conventional indicators. It displays analog signal (mV) input from the loadcell into engineering values. With the help of the keypad and display, unit allows to set and modify various configuration parameters and calibration.

General Specifications of this unit are:

- On board 24-bit ADC is provided for Digitising Analog Input.
- Filtering: Analog & Digital
- Sampling speed: 15 readings/second
- Power Supply: 24 VDC
- Input: 4-wire Load cell, Up to Four Single Load cell with 300 Ohms Resistor
- Remote input for GROSS/NET, TARE and Zero functions
- Display: **6-digit 7-segment 0.56" Red LED**
- Decimal position: Selectable.
- Key board: Four keys membrane like
- Programmable Parameters:
 - Decimal Point, Capacity, Display Resolution, Grad, Zero Track Band, Zero Range
- Configuration Data are stored in serial NVRAM, Battery back up not required
- Calibration through software (Offset: 'Z' & Span: 'S' stored in NVRAM)
- Optional:
 - Serial Port for communication with the remote display/Printer/Computer using RS-485/RS-232
 - Outputs: One Digital output (opto isolator)
 - Retransmission: 4-20 mA/0-10V Proportional indicated weight
- Enclosure: Plastic, General Purpose, Panel Mounting type
- Dimension:
 - Outer: 96 mm (W) x 48 mm (H) x 110 mm (D)
 - Cut-out: 92 mm (W) x 44 mm (H)

Samyak Instrumentation Pvt. Ltd.

F/4, Memnagar Complex, Opp. Petrol Pump, Memnagar, Ahmedabad-380 052, India

Phone: 91-79-27495500/5600 Fax: +91-79-27417997

E-mail: sales@samyak.com url: www.samyak.co.in
