

FLOW INDICATOR TOTALISER SMIT 1508**FEATURES:**

- MICROCONTROLLER BASED
- Input: Pulse (0 to 10 KHz) or Analog: 4.0-20.0mA, 0-20 ma, 0-5 V, 1-5 V
- Isolation between input & Output
- Four Keys
- Dual 7-segment red LED Display:
 - Flow rate: 0.56", 4/5 –digit (Display range: 0 to 19999)
 - Totaliser: 0.39", 8-digit (Display range: 0 to 99999999)
- Operating Voltage: 24 VDC / 12 VDC
- Transmitter Power supply: 24VDC/50 mA
- Programmable parameters: Zero, Full scale, Decimal position, Time Base for Totaliser, Conversion factor, K-Factor
- Non-volatile Memory for storing totaliser & other parameters
- Totaliser reset thro' Keypad (Password protected)
- Field Calibration of Input and retransmission output thro' software
- Accuracy:
 - For Rate display: +/- 0.25% of fullscale+1 digit,
 - For Totaliser: +/- 0.45% of fullscale+1 digit
- **OPTIONS:**
 - Serial Interface: RS-232/RS-485 (MODBUS protocol supported)
 - Isolated re-transmission

Samyak Instrumentation Pvt. Ltd.

F/4, Memnagar Complex, Opp. Petrol Pump, Memnagar, Ahmedabad-380 052, India
Phone: 91-79-27495500/5600, E-mail: sales@samyak.com url: www.samyak.co.in